



Model
MD 32 C/N-TW - HT322

TWEETER

Code 719901

Date 09/02/2012

General Specifications

Throat Diameter			
Nominal Impedance	8	Ω	
Voice coil resistance	5,45	Ω±	0,4 Ω
Minimum Impedance	5,8	Ω±	Ω
Power handling (AES) ⁽¹⁾	150	Watt	
Continuous Power Handling	300	Watt	
Voice Coil Diameter	32	mm	1,50 in
S.P.L. (1w,1m)	94	dB±	1,5 dB
Nominal Fs	1130	Hz±	120 Hz
Flux Density	1,31	T±	0,1 T
Crossover Frequency	2000 Hz 12dB/oct		
Frequency Range	2k-20k Hz		

(1) Life Test

Horn
 Input Signal Pink noise
 Band Pass Filter 2000-20000Hz,12dB/oct
 V on Speaker 30 V
 Test duration 2 hours

Key Features

Shorting copper cap for extended frequency response
 Neodymium ring magnet structure

Miscellaneous

Materials

Basket Material	Aluminium Flange
Voice Coil Former	Kapton
Voice Coil Wire	Aluminium
Membrane Material	Polyester
Membrane Shape	Dome
Surround Material	Polyester
Surround Shape	Half roll
Magnet Type	Neodymium
Magnet Weigth	86 g

Mechanical Data

Weight	460 g
Overall Diameter	110 mm
Overall Depth	32 mm
Baffle Cut Diameter	83 mm
Mounting holes number	4
Mounting holes diameter	5 mm
Mounting bolt diameter	96mm

